


Vector \$10 Patriot Crash-Rated Bollard - R-1010-\$10









- EMBEDMENT DETAILS ARE FOR REFERENCE ILLUSTRATION ONLY. MINIMUM FOUNDATION SIZES DEPEND ON LOCAL SOIL CONDITIONS, WEATHER CONDITIONS, AND ENGINEERING REQUIREMENTS.
- BOLLARD IS PROVIDED AS SHOWN, WITH PARTS LISTED BELOW. CONCRETE FOUNDATION AND/OR INSTALLATION NOT PROVIDED BY RELIANCE FOUNDRY.
- THIS DRAWING IS NOT DRAWN TO SCALE. DIMENSIONS PROVIDED HEREIN IS FOR REFERENCE ONLY. PLEASE CONSULT RELIANCE FOUNDRY SALES PROFESSIONALS IF ANY DIMENSION IS CRITICAL TO YOUR PARTICULAR INSTALLATION.
- RELIANCE FOUNDRY RESERVES THE RIGHT TO AMEND DESIGN AND SPECIFICATIONS WITHOUT PRIOR NOTICE FOR PRODUCT IMPROVEMENT.

INDIVIDUAL **DESCRIPTION MATERIAL ITEM** QTY | PART NUMBER WEIGHT (LB) 2500021 STEEL S10 FIXED BOLLARD ASSEMBLY 128 DO NOT SCALE DRAWING REVIEWED



General Description:

The made-in-America Vector \$10 Patriot Bollard delivers certified protection for storefronts, meeting ASTM F3016 S10 standards for low-speed vehicle impact with a P1 penetration rating. Designed for both safety and style, the distinctive form and curved profile enhance strength while distributing impact forces efficiently. These storefront safety bollards require no rebar, simplifying setup and reducing costs without compromising reliability. Domestic manufacturing shortens lead-times and lowers shipping costs, all while supporting U.S. supply chains.

Specifications:

Total Height: 65" [1651 mm]

Height Above Grade: 32" [813 mm]

Height Below Grade: 33" [838 mm]

Weight: 128 lbs [58 kg]

Material: Steel

Finish Options:

- Hot-dip Galvanised
- Primed Black

For more information on bollard installation, please visit: https://www.reliance-foundry.com/bollard/vector-fixed-<u>installation</u>





Unit 207, 6450 - 148 Street, Surrey, BC V3S 7G7, Canada 1-877-789-3245 info@reliance-foundry.com www.reliance-foundry.com

TITLE:

S10 FIXED BOLLARD INSTALLATION

SIZE DWG: 2500021-01 REV PART: 01B 2025-07-14 DRAWN ASM: 2500021 MS 2025-07-14 SCALE: 1:12 SHEET 1 OF 2

COPYRIGHT RESERVED THIS PLAN DRAWING AND DESIGN ARE, AND AT ALL TIMES REMAIN, THE EXCLUSIVE PROPERTY OF RELIANCE FOUNDRY CO. LTD.

Vector S10 Patriot Crash-Rated Bollard - R-1010-S10 TYPICAL BOLLARD ARRAY SHOWN (1 BOLLARD CAN WITHSTAND VEHICLE IMPACT ALONE) 48 [1219] O/C 12 305 **ADJUSTABLE** 12 305 24 610 TO JUNCTION BOX TENTATIVE ELECTRICAL IMPACT DIRECTION **CONDUIT ROUTING** IMPACT DIRECTION 32[813] MIN. 18 457 36 914 IN DEPTH **CONCRETE DEPTH** 65[1651] 33 838 3[76]



General Description:

The made-in-America Vector \$10 Patriot Bollard delivers certified protection for storefronts, meeting ASTM F3016 S10 standards for low-speed vehicle impact with a P1 penetration rating. Designed for both safety and style, the distinctive form and curved profile enhance strength while distributing impact forces efficiently. These storefront safety bollards require no rebar, simplifying setup and reducing costs without compromising reliability. Domestic manufacturing shortens lead-times and lowers shipping costs, all while supporting U.S. supply chains.

Specifications:

Total Height: 65" [1651 mm]

Height Above Grade: 32" [813 mm]

Height Below Grade: 33" [838 mm]

Weight: 128 lbs [58 kg]

Material: Steel

Finish Options:

- Hot-dip Galvanised
- Primed Black

For more information on bollard installation, please visit: https://www.reliance-foundry.com/bollard/vector-fixed-<u>installation</u>



Unit 207, 6450 - 148 Street, Surrey, BC V3S 7G7, Canada 1-877-789-3245 info@reliance-foundry.com www.reliance-foundry.com

TITLE:

S10 FIXED BOLLARD INSTALLATION

SIZE DWG: 2500021-01 REV 01B 2025-07-14 MS 2025-07-14 SCALE: 1:15 SHEET 2 OF 2

NOTES:

EMBEDMENT DETAILS ARE FOR REFERENCE ILLUSTRATION ONLY. MINIMUM FOUNDATION SIZES DEPEND ON LOCAL SOIL CONDITIONS, WEATHER CONDITIONS, AND ENGINEERING REQUIREMENTS.

4000 PSI (MIN.) CONCRETE FOUNDATION

- BOLLARD IS PROVIDED AS SHOWN, WITH PARTS LISTED BELOW. CONCRETE FOUNDATION AND/OR INSTALLATION NOT PROVIDED BY RELIANCE FOUNDRY.
- THIS DRAWING IS NOT DRAWN TO SCALE. DIMENSIONS PROVIDED HEREIN IS FOR REFERENCE ONLY. PLEASE CONSULT RELIANCE FOUNDRY SALES PROFESSIONALS IF ANY DIMENSION IS CRITICAL TO YOUR PARTICULAR INSTALLATION.
- RELIANCE FOUNDRY RESERVES THE RIGHT TO AMEND DESIGN AND SPECIFICATIONS WITHOUT PRIOR NOTICE FOR PRODUCT IMPROVEMENT.

	ITEM	QTY	PART NUMBER	DESCRIPTION	MATERIAL	INDIVIDUAL WEIGHT (LB)	
	1	3	2500021	S10 FIXED BOLLARD ASSEMBLY	STEEL	128	DRAWN
SIGN ARE, AND AT ALL TIMES REMAIN, THE EXCLUSIVE PROPERTY OF RELIANCE FOUNDRY CO. LTD. DO NOT SCALE DRAWING							REVIEWED

COPYRIGHT RESERVED THIS PLAN DRAWING AND DESIGN ARE, AND AT ALL TIMES REMAIN, THE EXCLUSIVE PROPERTY OF RELIANCE FOUNDRY CO. LTD.

TENTATIVE ELECTRICA CONDUIT ROUTING