



Bike Rack, R-8239-FL Drop-in Anchor Installation: 1) Use a carbide tip drill bit (conforming to ANSI B 212.15) to drill 5/8" x 2" hole (dia. x depth) 2) Clean drill hole of debris 3) Insert anchor into drill hole General Description: 4) Use hammer and proper setting tool* (for 1/2" Drop-In Anchor from UCAN) to drive plug down 5) Fasten button head screw (Maximum torque 22 ft x lbf) The R-8239-FL Wave Bike Rack is a high-capacity, corral-style bike stand that accommodates up to 5 bikes at * Substitute a narrow punch tool at installer's risk a time. Bikes can be secured using a U-lock or cable between the frame and front or rear wheel. Wave bike racks are made from carbon steel and feature durable powder coatings to prevent corrosion and wear. Select from 1 of 6 custom colors. Bolt-down flanges for existing concrete surfaces. Specifications: 38 7/8 Height: 36" Cross Span: 39" Ø2 3/8-Weight: 45 lbs Material: Steel Finish Options: ✓ Polyester Powdercoated See Reliance Foundry's standard color options at www.reliance-foundry.com/bollard/colors-bollards Grade 2 1/2 Notes: • Embedment details are for reference illustration only. Minimum foundation sizes depend on local soil conditions, weather conditions and engineering requirements. • Bike rack is provided as shown with parts listed below. Concrete foundation and/or installation not provided by Reliance Foundry. • This drawing is not drawn to scale. Dimensions provided herein are for reference only. Please consult Reliance Foundry sales professionals if any dimension is critical **RELIANCE FOUNDRY** to your particular installation. — SINCE 1925 — • Reliance Foundry reserves the right to amend design and specifications without prior notice for product improvement. Unit 207, 6450 - 148 Street, Surrey, BC V3S 7G7, Canada 1-877-789-3245 info@reliance-foundry.com www.reliance-foundry.com TITLE PARTS LIST Bike Rack, R-8239-FL **ITEM** QTY PART NUMBER DESCRIPTION **MATERIAL** WEIGHT R8239FL Bike Rack R8239FL Steel Powder Coated 45 lbs 1 Stainless Steel Washer 1/2" Stainless Steel Washer 1/2" OD 1 1/4" Thick .05" Stainless Steel

Hexagon Socket Button Head Cap Bolt 1/2" x 1 1/4" - requires 5/16" hex key

4

Drop-in Concrete Insert 1/2" - requires 5/8" x 2" hole (dia. x depth)

COPYRIGHT RESERVED THIS PLAN DRAWING AND DESIGN ARE, AND AT ALL TIMES REMAIN, THE EXCLUSIVE PROPERTY OF RELIANCE FOUNDRY CO. LTD.

6

6

3

Button Head Bolt 1/2" x 1 1/4"

Drop-in Concrete Insert 1/2"

DWG NO

R8239FL

C1

SHEET 1 OF 2

SIZE

NOT TO SCALE

1/8 lbs

1/8 lbs

Stainless Steel

Steel Plated

